

30" RING BUOY

DX0340D Bridgebuoy®

DX0340D

TYPE

Type IV U.S.C.G., global approval for 30" Ring Buoy

USES

The only "Bridgebuoy®", it is used onboard commercial vessels, offshore installations and larger yachts. All Datrex rings are molded from high impact linear low-density polyethylene for superior life expectancy in the most severe environments. These 4kg Life Buoy Rings are suitable for commercial shipping applications only, and are designed to be used in conjunction with SOLAS MOB Smoke & Light Markers fitted onto the sides of commercial ships. The extra weight ensures that the MOB Smoke & Light Marker is pulled from its bracket once the lifebuoy is released over the side of the vessel. Fully SOLAS / Ships Wheel approved and fitted as standard with 8 x SOLAS Retro Reflective tapes and lifebuoy grab lines. **Drop tested up to 100 meters.**

FEATURES

All Datrex rings are molded from high impact linear low-density polyethylene for superior life expectancy in the most severe environments. The encircling black, floating rope is replaceable.

SPECIFICATIONS

ITEM NO.	DX0340D
USE	Marine safety
SIZE	30" (76 cm)
WEIGHT	Min. weight 4 kg
CLOSED CELL FOAM	Yes
MOLD RESISTANT	Yes
RETRO-REFLECTIVE	Yes
COLOR	International Orange
QUANTITY PER CASE	3 per case
CASE DIMENSIONS	31 x 31 x 13 inches (63.5 x 63.5 x 25.4 cm)
CASE WEIGHT	34 lbs (15.4 kg)
QUANTITY PER PALLET	27 liferings
PALLET DIMENSIONS	43 x 48 x 65 inches (102 x 122 x 140 cm)
PALLET WEIGHT	306 lbs (139 kg)
PALLET VOLUME	78 ft ³ (2.20 m ³)



APPROVAL/COMPLIANCE

Approved globally with USCG, Canadian Coast Guard (TC) and DNV GL. U.S.C.G. Approval No: 160.050/128/0, U.S.C.G. SOLAS 16

